

ENG

# VDI100 NEW

## GENERAL PURPOSE FULL VECTOR INVERTER



Code 82261L

**GEFRAN**  
BEYOND TECHNOLOGY

# GEFRAN

BEYOND TECHNOLOGY

Over fifty years of experience, an organisation highly focused on the customer's needs and constant technological innovation make Gefran a benchmark in the design and production of sensors and components for industrial process automation and control.

Expertise, flexibility and process quality are the factors that distinguish Gefran in the production of integrated tools and systems for specific applications in various industrial fields, with consolidated know-how in the plastics, mobile hydraulics, heating and lift sectors.

Technology, innovation and versatility represent the catalogue's added value in addition to the ability to create specific application solutions in association with the world's leading machine manufacturers.



# APPLICATIONS



CONVEYOR AND TRANSPORTATION MACHINERY



PAPER MAKING MACHINE



MACHINE TOOL/METAL PROCESSING MACHINERY



WOOD WORKING MACHINERY



HVAC AND PUMP SYSTEMS



PAPER/TEXTILE MACHINE



GRAVITATIONAL HANDLING EQUIPMENT



PLASTICS / RUBBER PROCESSING MACHINE



WIRE / CABLE MAKING MACHINE

In addition to foreseeing the market's application needs, Gefran forms partnerships with its customers to find **the best way to optimise and boost the performance of various applications**.

Gefran products communicate with one another to provide integrated solutions, and can dialogue with devices by other companies thanks to compatibility with numerous fieldbuses.

**Modbus**

**PROFINET<sup>®</sup>  
BUS**

**CANopen**

**DeviceNet**

## DESCRIPTION



The GEFRAN range of VDI100 inverters is specifically designed to give the utmost flexibility of application to modern automation systems and ensure ease of use, while guaranteeing advanced control capabilities for both asynchronous and permanent magnet SPM and IPM motors.

VDI100 inverter features an intuitive and user friendly interface to enable immediate motor start-up and system functions to implement control architectures for the most advanced application solutions, all with maximum energy efficiency.


The VDI100 series offer a perfect automation system integration with "universal" standard configuration, optional cards and accessories. All these elements offer real advantages in terms of product and system optimization and cost saving.

- > Wide motor control capability
- > Advanced auto-tuning
- > High level sensor vector mode
- > Fast computing ability
- > Conformity to global standards.

## POWER RANGE

kW (Hp)	Power											
	0.75 (1.0)	1.5 (2.0)	2.2 (3.0)	3.7 (5.0)	5.5 (7.5)	7.5 (10)	11 (15)	15 (20)	18.5 (25)	22 (30)	30 (40)	37 (50)
230 Vac, 3ph	Size 1		Size 2			S.3	Size 4			-		
400 Vac, 3ph	Size 1		Size 2			Size 3			Size 4		Size 5	
400 Vac -F, 3ph	Size 1		Size 2			Size 3	Size 4			Size 5		

## DRIVE TYPE DESIGNATION



## WEIGHTS AND DIMENSIONS

Mechanical size - Protection degree	Dimensions: Width x Height x Depth		Weight	
	mm	inches	kg	lbs
1 - IP20/NEMA1	130 x 215 (306*) x 150	5.12 x 8.46 (12.05*) x 5.91	2.2 (3.5*)	4.8 (7.7*)
2 - IP20/NEMA1	140 x 279.5 (400*) x 181	5.51 x 11.00 (15.75*) x 7.13	3.8 (5.5*)	8.4 (12.1*)
3 - IP20/NEMA1	210 x 300 (416.5*) x 215	8.27 x 11.81 (16.40*) x 8.46	6.2 (8*)	13.7 (17.6*)
4 - IP20/NEMA1	265 x 360 (500*) x 225	10.43 x 14.17 (19.68*) x 8.86	10 (12.5*)	22 (27.5*)
5 - IP20/NEMA1	288 x 526 (680*) x 252 <sup>(1)</sup> / 272 <sup>(2)</sup>	11.34 x 20.67 (26.77*) x 9.92 <sup>(1)</sup> / 10.70 <sup>(2)</sup>	27 (32*)	59.5 (70.5*)

\* with filter

(1) VDI100-5300-KBX-4/4F

(2) VDI100-5370-KXX-4 / VDI100-5450-KXX-4/4F

# GENERAL CHARACTERISTICS

<b>Control Characteristics</b>	Motor type	Asynchronous and Synchronous Motor (Surface Permanent Magnet Motor, Interior Permanent Magnet Motor)
	Control Modes (1)	V/f, V/f+Encoder, SLV (vector control open loop), SV (vector control closed loop), PMSLV (vector control open loop for Permanent Magnet Motor, PMSV (vector control closed loop for Permanent Magnet Motor)
	Speed control accuracy	±1% (SLV, overload 200% and control range 1: 30 (60...2Hz ; 50...1.6Hz)), ±1% (SLV, overload 150% and control range 1: 50 (60...1.2Hz ; 50...1Hz)), ±1.5% (V/f open-loop, overload 150% and control range 1: 40 / 60...1.5Hz ; 50...1.25Hz), ±0.1% (SV)
	Output Frequency range	0.1Hz~599Hz
	Output Frequency Resolution	0.01Hz
	Overload Tolerance (1)	• <b>Heavy Duty Mode</b> (HD.): 150% rated current for 60sec, 200% rated current for 2 sec. (Factory default) • <b>Normal Duty Mode</b> (ND.): 120% rated current for 60sec
	Frequency Setting Signal	0 to +10V, -10V to +10V, 4 to 20mA or pulse train input
	Acceleration / Deceleration Time	0.0 ~ 6000.0 sec (separate acceleration and deceleration time set)
	Voltage / Frequency Characteristics	15 fixed + one customized V/f pattern
	Braking Unit	Built-in braking transistor on 0.75-30kW HD
	Display	LED keypad with 5-digits 7-segment display (LCD keypad option)
	Main Control Functions	Auto-tuning, Zero Servo, Torque Control, Position Control, Droop, Soft-PWM, Over-Voltage Protection, Dynamic Braking, Speed Search, Frequency Traversing, Momentary Power Loss Restart, PID Control, Automatic Torque Compensation, Slip Compensation, RS-485 Communication, Close Loop Control with encoder, Simple PLC Function, 2 Analog Output, Run Permissive inputs, Application Presets, Real-time clock function, Fire mode function (for HVAC application).
	Safety function	STO SIL 2 (IEC 61508 and EN 61800-5-2)
	Other Functions	Records of Power ON and Operation Time, 4 Fault History Records and Latest Fault State Record, Energy-Saving Function, Phase Loss Protection, DC Braking, Mechanical Brake Control, Dwell, S Curve Acceleration and Deceleration, Pulse input / output, Display of Engineering Unit, NPN / PNP Selection
<b>Protection Functions</b>	Stall Prevention	During Acceleration, Deceleration and continuous run
	Over Current (OC) and Output Short-Circuit (SC) Protection	When the current exceeds 200% of the inverter rated current
	Inverter Overload Protection (OL2)	Inverter stops when the output is higher than below conditions. • <b>Heavy Duty Mode</b> (HD.): 150% rated current for 60sec, 200% rated current for 2 sec. (Factory default), Carrier frequency is from 2kHz to 8kHz • <b>Normal Duty Mode</b> (ND.): 120% rated current for 60sec, Carrier frequency is 2kHz
	Motor Overload Protection (OL1)	Electrical overload protection curve
	Over Voltage Protection (OV)	OV threshold = 410Vdc (230V class), 820Vdc (400V class)
	Under Voltage (UV)	UV threshold = 190Vdc (230V class), 380Vdc (400V class)
	Momentary Power Loss Restart	When Power loss exceeds 15ms. This function can be set up to 2 sec
	Overheat Protection (OH)	Thermistor sensor on heatsink
	Ground Fault Protection (GF)	Protection by current detection circuit
	Charge Indicator	When main circuit DC voltage ≥ 50V, the CHARGE LED is on
<b>Environment Specification</b>	Output Phase Loss Protection (OPL)	If the OPL function acts, the motor stops rotation automatically
	Protection degree	IP20 / NEMA 1, with standard removable anti dust cover
	Operating Temperature	-10~+50°C (without anti dust cover) -10~+40°C (with anti dust cover) Up to +60°C with derating (0.75 ~ 22 kW) / Up to +50°C with derating (30 ~ 45 kW)
	Storage Temperature	-20 ~ +70°C
	Humidity	95% RH or less (no condensation)
	Altitude	1000m (3281ft) or below without de-rating; 1000~3000m (9843ft) with de-rating
	Vibration	1.0G, in compliance with IEC 60068-2-6
	Pollution Degree	Meet IEC 60721-3-3 Class 3C2
<b>Communication Function</b>	Built-in: RS-485 with Modbus RTU / ASCII (standard RJ45 connection) Optional: Profibus/CANopen/DeviceNet/TCP-IP	
	EMI filter	Add-on module on -F version 0.75-45kW HD In compliance with EN61800-3 standard
<b>Certification</b>	<b>CE RoHS</b>	Complies with the EC Directive concerning low voltage equipment (Directives LVD 2014/35/EC, EMC 2014/30/EC) In compliance with EN61800-3 (CE & RE) and EN61800-5-1 (LVD) Conformity to RoHS directive
	<b>cULus</b>	UL508C
<b>Encoder expansion card (optional)</b>		Asynchronous Motor: Digital incremental Line driver and Open collector, Resolver PM motor: Digital incremental Line driver, Resolver, SinCos
<b>Other optional cards</b>		Profibus DP (EXP-PDP-VDI100), CANopen (EXP-CAN-VDI100), EtherCAT (EXP-CAT-VDI100), Digital & analog I/O (EXP-I/O-VDI100), DC24V power supply (EXP-24V-VDI100)

(1) The V/f, V/f+Encoder, and SLV control modes can be used with ND Overload. See the instruction manual for further information.

# GENERAL CHARACTERISTICS

## SMART FUNCTIONS INTEGRATED

VDI100 integrates intelligent functions to simplify system integration, reduce costs and improve comfort in industrial environment.

- > Intelligent over voltage suppression
- > Advanced motor auto-tune
- > Ultra low motor noise with Soft-PWM
- > Application presets.



## I/O CONFIGURATION

The VDI100 inverter features a standard I/O card specially developed to give maximum flexibility for the user.

- > Digital input: 8, NPN/PNP
- > Digital output: 1
- > Analog input: 2, AI1: -10~10V / 0~10V / 4~20mA, AI2: 0~10V / 4~20mA
- > Analog output: 2, AO1:0~10V, AO2:0~10V/4~20mA
- > Relay output: 1 (size 1) / 2 (all other sizes)
- > Others: PTC input (AI2), Pulse input (32kHz), Pulse output (32kHz).

The configuration can be expanded with the optional internal card **EXP-I/O-VDI100**: 1 AI (-10 ... +10V / 4 ... 20 mA) , 2 DO relays (250V AC 1A max) and 2 DO.



## ROBUST DESIGN


Coated PCB offers protection for harsh environments.

All models have fan cooled external heatsinks which eliminate ingress of dust.

## Modbus

## SERIAL COMMUNICATION

The VDI100 integrates a standard RS485 serial line with Modbus RTU/ASCII protocol, for peer-to-peer or multidrop connections.



## DUAL CORE PROCESSORS

High Performance & Reliability.

### • 32Bit MCU

Mass computing capability for advanced current vector control technology.  
Minimizes the internal loop time for higher control response.

### • ASIC (from size 2)

Prevents inrush current damage to IGBT module.  
Enhances the reliability and life expectancy of motor drive.

## “UNIVERSAL” IN MOTOR TECHNOLOGIES

Simple parameter settings for easy switching between asynchronous and permanent magnet motors.

High performance current vector control for a wide range of motors types.



### Asynchronous Motor

- > Competitive
- > Mechanical Robustness



### Surface Permanent Magnet Motors (SPM)

- > High Efficiency
- > High power density
- > Low Cogging Torque



### Interior Permanent Magnet Motors (IPM)

- > Highly Efficient
- > Compact Size
- > With Reluctance Torque

# VDI100 GENERAL PURPOSE FULL VECTOR INVERTER

## FAN CONTROL AND EASY MAINTENANCE

Fan control achieves low noise levels and long-lasting fan.

Easy access to fan allows simple and quick maintenance and replacement.



## INTEGRATED KEYPAD

The integrated programming keypad with 5 Digit 7 Segment LED display provide fast programming and immediate start-up.

## OPTIONAL LCD PROGRAMMING KEYPAD

The optional LCD programming keypad with clear and wide parameter display in multiple languages, makes the VDI100 extremely intuitive and easy to use.

The keypad can also be used remotely and as a copy unit to copy parameter settings from one drive to an other.

## FIELDBUS

The VDI100 can be easily integrated into machine architectures through Profibus, CANopen, EtherCAT and DeviceNet communication options.

Model	Description
EXP-PDP-VDI100	Profibus DP interface internal card
EXP-DN-BDI/VDI	DeviceNet interface external module
EXP-CAN-VDI100	CanBus interface internal card
EXP-CAT-VDI100	Ethercat interface internal card

\* The Middle layer case option is required.



## EXTERNAL +24V POWER SUPPLY

Powered by an external DC power supply, the optional card, **EXP-24V-VDI100**, supplies the control board with +24V power, thus ensuring that control is maintained even when the mains power supply is cut off or presents anomalies.



## RJ45 TO USB CONNECTING CABLE

For the connection between inverter and PC using Gf\_exPress and PC Tools configurator (length 1.8 m).

## COPY UNIT

- > Copying parameters settings from one AC drive to another.
- > Standard RJ45 interface cable (2 m. included).



## ENCODER FEEDBACK EXPANSION CARDS

### > EXP-OC-VDI100

Digital incremental open collector encoder card.

- For Asynchronous motor
- Support Open Collector type and pulse signal

Terminals	Description
Vcc	Power Supply for encoder: 12V/5V±5%, 200mA
GND, /A, /B, /Z	Power Source and Input Signal Common
A, B, Z	Encoder Signal Input Terminal (Open Collector Type)
AO, BO, ZO,	Pulse monitor output: Open Collector Type, 24V, 30mA
/AO, /BO, /ZO	Output Signal Common
E	Shielding connection

### > EXP-LD-VDI100

Digital incremental Line driver encoder card.

- For Asynchronous motor
- Support Line Driver type and complementary type pulse signal

Terminals	Description
Vcc	Power Supply for encoder: 12V/5V±5%, 200mA
GND	Power Source and Input Signal Common
A, /A, B, /B, Z, /Z	Encoder Signal Input Terminal (Line Driver Type), RS-422 Level Output
AO, /AO, BO, /BO, ZO, /ZO	Pulse monitor output: Line Driver Type, RS-422 Level Input
E	Shielding connection

### > EXP-LD-PM-VDI100

Digital incremental Line driver encoder card with Hall sensor.

- For Permanent Magnet motor
- Support Line Driver type and complementary type pulse signal

Terminals	Description
Vcc	Power Supply for encoder: 5V±5%, 200mA
GND	Power Source and Input Signal Common
A, /A, B, /B, Z, /Z, U, /U, V, /V, W, /W	Encoder Signal Input Terminal (Line Driver Type), RS-422 Level Input
AO, /AO, BO, /BO, ZO, /ZO	Pulse monitor output: Line Driver Type, RS-422 Level Output
E	Shielding connection

### > EXP-RS-PM-VDI100 (\*)

Resolver card for SPM / IPM Permanent Magnet motor and Asynchronous.

Terminals	Description
R1, R2, S1, S2, S3, S4	R1-R2: Sinusoidal excitation signal. 7Vrms, 10kHz. Transformation ratio: 0.5±5% S1-S3: analog input of Sine signal. S2-S4: analog input of Cosine signal.
AO, /AO, BO, /BO, ZO, /ZO	A and B phase output terminal; Z phase monitoring output terminal. Line Driver output type: RS-422 Level output
E	Shielding connection


(\*) this card is not applicable on size 1 models: VDI100-1007...1022-KBX--4

### > EXP-SC-PM-VDI100

SinCos encoder card for Permanent Magnet motor

Terminals	Description
ESV	Power supply for encoder 5V±5%, 200mA
GND	Power supply common
C+, C-	Input C pulse from the encoder, Vpp= 0.6-1.2V
D+, D-	Input D pulse from the encoder, Vpp= 0.6-1.2V
A+, A-	Input A pulse from the enc., Vpp= 0.6-1.2V, fmax=20KHz
B+, B-	Input B pulse from the enc. Vpp= 0.6-1.2V, fmax=20KHz
R+, R-	Input R pulse (encoder home pulse)
a+, a-	Output a ratio of the A pulse frequency
b+, b-	Output b ratio of the B pulse frequency
E, E	Shielding connection: wire and inverter terminal "E"

# WIRING DIAGRAM



- (1) The main circuit of 0.75-22kW (included) with built-in braking transistor provide terminal B2. The braking resistor can be connected directly between B1 and B2. Optional braking module is available for the other models.
- (2) The multi-function digital input terminals S1-S8 can be set to Source (PNP) or Sink (NPN) mode by SW6 switch.
- (3) Multi-function analog input 2 (AI2) can be set to the voltage command input (0~10/~-10V) or the current command input (4~20mA) through SW4 switch.
- (4) When integrated Run Permissive inputs NOT used, connect a link across terminals SF1/ SF2 and SG. External safety circuits can be interfaced with inverter using terminals SF1/ SF2 and SG.
- (5) Terminals -10V S(+), S(-), R2A-R2C and PO-GND are provided for 3.7kW ratings or above.
- (6) A01/A02 default setting is 0~+10V.
- (7) Only the model 2.2-18.5kW (2T) and 3.7-45kW (-4) provide P1 terminal, for external DC choke connected between P1 and P2. P1 and P2 are short-circuited by the factory.
- (8) It need turn on the switch for the terminal resistor RS485 in the last inverter when many inverters in parallel connection.

# CHOOSING THE INVERTER: INPUT AND OUTPUT DATA

## THREE PHASE - 230V CLASS

Sizes VDI100			1007	1015	2022	2037	2055	3075	4110	4150	4185	
Output Rating (2)	HD (3)	Rated Output Capacity KVA	1.9	3	4.2	6.7	9.5	12.6	17.9	22.9	27.8	
		Rated Output Current A	5	8	11	17.5	25	33	47	60	73	
		Maximum Applicable Motor (1)	1	2	3	5	7.5	10	15	20	25	
	ND (4)	kW	0.75	1.5	2.2	3.7	5.5	7.5	11	15	18.5	
		Rated Output Capacity KVA	2.3	3.7	4.6	8.4	11.4	16.0	21.3	26.3	30.1	
		Rated Output Current A	6	9.6	12	22	30	42	56	69	80	
	Maximum Applicable Motor (1)	HP	2	3	5	7.5	10	15	20	25	30	
		kW	1.5	2.2	3.7	5.5	7.5	11	15	18.5	22	
Maximum Output Voltage		V	Three-Phase, 200V ~ 240V									
Maximum Output Frequency		Hz	0.1~599 (Based on parameter setting)									
Input Power	Rated Voltage, Frequency		Three-Phase, 200V ~ 240V, 50/60Hz									
	Allowable Voltage Fluctuation		-15% ~ +10%									
	Allowable Frequency Fluctuation		±5%									
	HD	Rated Input Current A	5.4	8.5	11.7	18.7	26.3	34.5	51.1	65.2	79.4	
		ND	6.5	9.6	12.8	22.3	31.6	41.7	60.9	75	85.9	
Powerloss	Watt Loss W		107.0	145.5	166.6	288.0	461.2	600.3	733.1	961.7	1021.3	
	Heat Loss kcal/hr		92.1	125.1	143.2	247.7	396.7	516.3	630.5	827.1	878.3	
	Switching Frequency kHz		8	8	8	8	8	8	8	8	8	
	Braking Transistor		Built-in									

## THREE PHASE - 400V CLASS

Sizes VDI100			1007	1015	1022	2037	2055	3075	3110	3150 4150-F	4185	4220	5300	5370	5450
Output Rating (2)	HD (3)	Rated Output Capacity KVA	2.6	3.2	4.2	7	11.3	13.7	18.3	23.6	29.7	34.3	45.7	57.2	69.3
		Rated Output Current A	3.4	4.2	5.5	9.2	14.8	18	24	31	39	45	60	75	91
		Maximum Applicable Motor (1)	1	2	3	5	7.5	10	15	20	25	30	40	50	60
	ND (4)	Rated Output Capacity KVA	3.1	4.1	5.3	9.2	13.3	17.5	23.6	29.0	33.5	44.2	55.6	67.1	78.5
		Rated Output Current A	4.1	5.4	6.9	12.1	17.5	23	31	38	44	58	73	88	103
		Maximum Applicable Motor (1)	2	3	5	7.5	10	15	20	25	30	40	50	60	75
	kW		1.5	2.2	3.7	5.5	7.5	11	15	18.5	22	30	37	45	55
Maximum Output Voltage		V	Three-Phase, 380V to 480V												
Maximum Output Frequency		Hz	0.1~599 (Based on parameter setting)												
Input Power	Rated Voltage, Frequency		Three-Phase, 380V to 480V, 50/60Hz												
	Allowable Voltage Fluctuation		-15% ~ +10%												
	Allowable Frequency Fluctuation		±5%												
	HD	Rated Input Current A	3.7	5.3	6	9.6	15.5	18.7	25	33.7	42.4	48.9	65.2	81.5	98.9
		ND	4.5	5.9	7.5	11.6	18.2	24	32.3	41.3	47.8	58.7	78.3	95.7	112
Powerloss	Watt Loss W		123.2	130.5	151.5	237.6	343.7	400.8	448.6	493.9	547.8	657.7	976.6	1157.9	1397.2
	Heat Loss kcal/hr		105.9	112.2	130.3	204.3	295.6	344.6	385.8	424.8	471.1	565.6	839.8	995.8	1201.6
	Switching Frequency kHz		8	8	8	8	8	8	8	8	8	8	5	5	5
	Braking Transistor		Built-in									Option (External Braking Module)			

Power	230 V Class	400 V Class	HD mode carrier freq range	HD mode carrier freq default setting
0.75 ~ 15 kW	0.75 ~ 22 kW		2~16 kHz	8 kHz
18.5 kW	-		2~12 kHz (5)	6 kHz
-	30 ~ 37 kW		2~12 kHz (5)	5 kHz
-	45 kW		2~10 kHz (5)	5 kHz

- (1) Based on the standard 4-pole induction motor. The selected inverter must have a higher output current rating than the motor.
- (2) The default setting of VDI100 is HD (heavy duty mode). To switch VDI100 to ND (normal duty mode) set parameter (00-27) to 1. When switching to ND (normal duty mode), the frequency will change to 2kHz.
- (3) The default setting of carrier frequency in HD mode is shown into the table on the right, if the setting value is higher than default setting, derating may be required.
- (4) The default setting of carrier frequency in ND mode is 2kHz, if the setting value is higher than default setting, de-rating may be required.
- (5) If control mode is set to SLV mode and maximum frequency is larger than 80Hz, the carrier frequency range is 2~8kHz.

# DRIVE MODELS & CODES

## THREE PHASE - 230V CLASS

- Without EMI filter
- BU built-in
- IP20 / NEMA 1

Code	Model	Pn@ 230 Vac		Configuration
		HD	ND	
S6N260	VDI100-1007-KBX-2T	0.75 kW	1.5 kW	Internal Braking Unit - External EMI filter
S6N261	VDI100-1015-KBX-2T	1.5 kW	2.2 kW	Internal Braking Unit - External EMI filter
S6N262	VDI100-2022-KBX-2T	2.2 kW	3.7 kW	Internal Braking Unit - External EMI filter
S6N263	VDI100-2037-KBX-2T	3.7 kW	5.5 kW	Internal Braking Unit - External EMI filter
S6N264	VDI100-2055-KBX-2T	5.5 kW	7.5 kW	Internal Braking Unit - External EMI filter
S6N265	VDI100-3075-KBX-2T	7.5 kW	11 kW	Internal Braking Unit - External EMI filter
S6N266	VDI100-4110-KBX-2T	11 kW	15 kW	Internal Braking Unit - External EMI filter
S6N267	VDI100-4150-KBX-2T	15 kW	18.5 kW	Internal Braking Unit - External EMI filter
S6N268	VDI100-4185-KBX-2T	18.5 kW	22 kW	Internal Braking Unit - External EMI filter

## THREE PHASE - 400V CLASS

- With built-in EMI filter
- BU built-in up to 30 kW
- IP20 / NEMA 1

Code	Model	Pn@ 400 Vac		Configuration
		HD	ND	
S6N269	VDI100-1007-KBX-4-F	0.75 kW	1.5 kW	Internal Braking Unit - With EMI filter
S6N270	VDI100-1015-KBX-4-F	1.5 kW	2.2 kW	Internal Braking Unit - With EMI filter
S6N271	VDI100-1022-KBX-4-F	2.2 kW	3.7 kW	Internal Braking Unit - With EMI filter
S6N272	VDI100-2037-KBX-4-F	3.7 kW	5.5 kW	Internal Braking Unit - With EMI filter
S6N273	VDI100-2055-KBX-4-F	5.5 kW	7.5 kW	Internal Braking Unit - With EMI filter
S6N274	VDI100-3075-KBX-4-F	7.5 kW	11 kW	Internal Braking Unit - With EMI filter
S6N275	VDI100-3110-KBX-4-F	11 kW	15 kW	Internal Braking Unit - With EMI filter
S6N276	VDI100-4150-KBX-4-F	15 kW	18.5 kW	Internal Braking Unit - With EMI filter
S6N277	VDI100-4185-KBX-4-F	18.5 kW	22 kW	Internal Braking Unit - With EMI filter
S6N278	VDI100-4220-KBX-4-F	22 kW	30 kW	Internal Braking Unit - With EMI filter
S6N279	VDI100-5300-KBX-4-F	30 kW	37 kW	Internal Braking Unit - With EMI filter
S6N280	VDI100-5370-KXX-4-F	37 kW	45 kW	With EMI filter
S6N281	VDI100-5450-KXX-4-F	45 kW	55 kW	With EMI filter

- Without EMI filter
- BU built-in up to 30 kW
- IP20 / NEMA 1

Code	Model	Pn@ 400 Vac		Configuration
		HD	ND	
S6N282	VDI100-1007-KBX-4	0.75 kW	1.5 kW	Internal Braking Unit - Without EMI filter
S6N283	VDI100-1015-KBX-4	1.5 kW	2.2 kW	Internal Braking Unit - Without EMI filter
S6N284	VDI100-1022-KBX-4	2.2 kW	3.7 kW	Internal Braking Unit - Without EMI filter
S6N285	VDI100-2037-KBX-4	3.7 kW	5.5 kW	Internal Braking Unit - Without EMI filter
S6N286	VDI100-2055-KBX-4	5.5 kW	7.5 kW	Internal Braking Unit - Without EMI filter
S6N287	VDI100-3075-KBX-4	7.5 kW	11 kW	Internal Braking Unit - Without EMI filter
S6N288	VDI100-3110-KBX-4	11 kW	15 kW	Internal Braking Unit - Without EMI filter
S6N289	VDI100-3150-KBX-4	15 kW	18.5 kW	Internal Braking Unit - Without EMI filter
S6N290	VDI100-4185-KBX-4	18.5 kW	22 kW	Internal Braking Unit - Without EMI filter
S6N291	VDI100-4220-KBX-4	22 kW	30 kW	Internal Braking Unit - Without EMI filter
S6N292	VDI100-5300-KBX-4	30 kW	37 kW	Internal Braking Unit - Without EMI filter
S6N293	VDI100-5370-KXX-4	37 kW	45 kW	Without EMI filter
S6N294	VDI100-5450-KXX-4	45 kW	55 kW	Without EMI filter

# ACCESSORIES AND OPTIONS

## INPUT CHOKE

Code	Model	Dimensions: WxHxD (mm)	Weight (kg)	For VDI100-....
------	-------	------------------------	-------------	-----------------

Input choke - Overload HD (150%) - Class 230V 3ph

S7FF7	LR3-005	150 x 155 x 85	6	1007
S7FF6	LR3-011	180 x 182 x 130	8	1015
S7AB6	LR3y-2075	150 x 155 x 79	4.9	2022
S7AB8	LR3y-3150	150 x 169 x 85	5.5	2037
S7FF4	LR3-022	180 x 182 x 130	7.8	2055
S7FF3	LR3-030	180 x 160 x 185	8.2	3075
S7FF2	LR3-037	180 x 160 x 185	9.5	4110
S7FF1	LR3-055	180 x 180 x 185	12	4150
S7FF1	LR3-055	180 x 180 x 185	12	4185

Input choke - Overload HD (150%) - Class 400V 3ph

S7AAE	LR3y-1015	120 x 125 x 65	1.8	1007
S7AAF	LR3y-1022	120 x 125 x 65	1.9	1015
S7AB3	LR3y-1030	120 x 125 x 65	1.9	1022
S7AAG	LR3y-2040	120 x 125 x 65	2	2037
S7AB6	LR3y-2075	150 x 155 x 79	4.9	2055
S7AB7	LR3y-3110	150 x 155 x 79	5	3075
S7AB8	LR3y-3150	150 x 169 x 85	5.5	3110
S7FF4	LR3-022	180 x 182 x 130	7.8	3150
S7FF4	LR3-022	180 x 182 x 130	7.8	4150
S7FF4	LR3-022	180 x 182 x 130	7.8	4185
S7FF3	LR3-030	180 x 160 x 185	8.2	4220
S7FF2	LR3-037	180 x 160 x 185	9.5	5300
S7FF1	LR3-055	180 x 180 x 185	12	5370
S7FF1	LR3-055	180 x 180 x 185	12	5450

Code	Model	Dimensions: WxHxD (mm)	Weight (kg)	For VDI100-....
------	-------	------------------------	-------------	-----------------

Input choke - Overload ND (120%) - Class 230V 3ph

S7AB6	LR3y-2075	150 x 155 x 79	4.9	1007
S7AB8	LR3y-3150	150 x 169 x 85	5.5	1015
S7FF4	LR3-022	180 x 182 x 130	7.8	2022
S7FF3	LR3-030	180 x 160 x 185	8.2	2055
S7FF2	LR3-037	180 x 180 x 185	9.5	3075
S7FF1	LR3-055	180 x 180 x 185	12	4110
S7D19	LR3-090	300 x 205 x 265	30	4150
S7D19	LR3-090	300 x 205 x 265	30	4185

Input choke - Overload ND (120%) - Class 400V 3ph

S7AB3	LR3y-1030	120 x 125 x 65	1.9	1007
S7AAG	LR3y-2040	120 x 125 x 65	3	1015
S7AB6	LR3y-2075	150 x 155 x 79	4.9	1022
S7AB7	LR3y-3110	150 x 155 x 79	5	2037
S7AB8	LR3y-3150	150 x 169 x 85	5.5	2055
S7FF4	LR3-022	180 x 182 x 130	7.8	3075
S7FF3	LR3-030	180 x 160 x 185	8.2	3110
S7FF3	LR3-030	180 x 160 x 185	8.2	3150
S7FF3	LR3-030	180 x 160 x 185	8.2	4150
S7FF2	LR3-037	180 x 160 x 185	9.5	4185
S7FF1	LR3-055	180 x 180 x 185	12	4220
S7FF1	LR3-055	180 x 180 x 185	12	5300
S7D19	LR3-090	300 x 205 x 265	30	5370
S7D19	LR3-090	300 x 205 x 265	30	5450

Mains choke listed in this table can only be used for the inverter input side. Do not connect Mains choke to the inverter output side.

## OUTPUT CHOKE

Code	Model	Finv_max [Hz]	Fswitch [kHz]	Dimensions WxHxD (mm)	Weight (kg)	For VDI100-....
------	-------	---------------	---------------	-----------------------	-------------	-----------------

Output Choke - Class 230V 3ph

S7FG1	LU3-001	400	20	120 x 128 x 71	2.7	1007
S7FG1	LU3-003	400	20	180 x 170 x 110	5.2	1015
S7FG3	LU3-005	400	20	180 x 170 x 110	5.8	2022
S7FG4	LU3-011	400	20	180 x 180 x 130	8	2037
S7FH2	LU3-015	400	20	180 x 160 x 170	7.5	2055
S7FH3	LU3-022	300	20	180 x 160 x 170	8	3075
S7FH4	LU3-030	300	15	180 x 160 x 180	9.5	4110
S7FH5	LU3-037	300	15	180 x 160 x 180	9.7	4150
S7FH5	LU3-037	300	15	180 x 160 x 180	9.7	4185

Output Choke - Class 400V 3ph

S7FG1	LU3-001	400	20	120 x 128 x 71	2.7	1007
S7FG1	LU3-001	400	20	120 x 128 x 71	2.7	1015
S7FG1	LU3-001	400	20	120 x 128 x 71	2.7	1022
S7FG3	LU3-005	400	20	180 x 170 x 110	5.2	2037
S7FG4	LU3-011	400	20	180 x 180 x 130	8	2055
S7FG4	LU3-011	400	20	180 x 180 x 130	8	3075
S7FH2	LU3-015	400	20	180 x 160 x 170	7.5	3110
S7FH3	LU3-022	300	20	180 x 160 x 170	8	3150
S7FH3	LU3-022	300	20	180 x 160 x 170	8	4150-F
S7FH3	LU3-022	300	20	180 x 160 x 170	8	4185
S7FH4	LU3-030	300	15	180 x 160 x 180	9.5	4220
S7FH5	LU3-037	300	15	180 x 160 x 180	9.7	5300
S7FH5	LU3-037	300	15	180 x 160 x 180	9.7	5370
S7FH6	LU3-055	300	15	240 x 210 x 180	14	5450

# ACCESSORIES AND OPTIONS

## BRAKING RESISTORS AND BRAKING UNIT

VDI100-....	Braking unit		Code	Type	Braking resistor		Dimensions - Weight W x H x d (mm) - (kg)	Braking torque (Peak / Continues) 10%ED	Minimum Resistance <sup>(1)</sup>	
	Model (Code)	Q.ty			Protection degree	Q.ty			(Ω)	(W)
<b>Class 230V 3ph</b>										
1007	-	-	S8T1DB	<b>RF 300 DT 200R</b>	IP44	1	260 x 106 x 47 - (1.4)	119%	17	1000
1015	-	-	S8SA15	<b>RF 200 100R</b>	IP44	1	300 x 27 x 27 - (0.57)	119%	17	1000
2022	-	-	S8SA14	<b>RF 200 68R</b>	IP44	1	300 x 36 x 27 - (0.57)	115%	17	1000
2037	-	-	S6F62	<b>RFH 600 40R</b>	IP44	1	320 x 27 x 36 - (0.6)	119%	17	1000
2055	-	-	S8SA27	<b>RFH 400 30R</b>	IP44	1	320 x 27 x 36 - (0.6)	108%	17	1000
3075	-	-	S8TOCZ	<b>RFPD 750 DT 26R</b>	IP44	1	200 x 106 x 70 - (1.7)	119%	11	1500
4110	-	-	S8SA33	<b>BRT 2K4 13R6</b>	IP20	1	440 x 180 x 220 - (7.5)	117%	11	1500
4150	-	-	S8TOOH	<b>BRT4K0-11R6</b>	IP20	1	625 x 100 x 250	119%	7	2400
4185	-	-	S8SA1	<b>RF 5K0 11R6</b>	IP20	1	545 x 200 x 200	119%	7	2400
<b>Class 400V 3ph</b>										
1007	-	-	S8SA26	<b>RFH 220 750R</b>	IP44	1	220 x 27 x 36 - (0.33)	126%	110Ω	700W
1015	-	-	S8TOCR	<b>RF 300 DT 400R</b>	IP44	1	260 x 106 x 47 - (1.4)	120%	110Ω	700W
1022	-	-	S8TOCP	<b>RF 220 T 250R</b>	IP44	1	300 x 36 x 27 - (0.5)	126%	93Ω	800W
2037	-	-	S6F64	<b>RFH 600 160R</b>	IP44	1	320 x 27 x 36 - (0.6)	126%	68Ω	1100W
2055	-	-	S8SA31	<b>RFMTX 400 130R</b>	IP44	1	580 x 140 x 110 - (4.2)	117%	41Ω	1800W
3075	-	-	S8TOCM	<b>RFPD 900 DT 100R</b>	IP44	1	260 x 106 x 70 (2.2)	120%	41Ω	1800W
3110	-	-	S8SA30	<b>BRT 1K6 52R</b>	IP20	1	580 x 140 x 110 - (4.2)	126%	41Ω	1800W
3150	-	-	S8SA29	<b>BRT 1K5 40R</b>	IP20	1	440 x 140 x 110 - (3)	120%	20.5Ω	3500W
4150	-	-	S8SA29	<b>BRT 1K5 40R</b>	IP20	1	440 x 140 x 110 - (3)	120%	13.5Ω	5300W
4185	-	-	S8SA36	<b>BRT 4K8 32R</b>	IP20	1	570 x 180 x 330 - (11)	118%	13.5Ω	5300W
4220	-	-	S8SA35	<b>BRT 4K8 27R2</b>	IP20	1	570 x 180 x 330 - (11)	120%	9.6Ω	7600W
5300	-	-	S8SA34	<b>BRT 6K 20R</b>	IP20	1	570 x 180 x 330 - (11)	122%	19.2Ω	3800W
5370	<b>BU-4-VDI100 (SGN143)</b>	2	S8SA36	<b>BRT 4K8 32R</b>	IP20	2	570 x 180 x 330 - (11)	120%	19.2Ω	3800W
5450	<b>BU-4-VDI100 (SGN143)</b>	2	S8SA35	<b>BRT 4K8 27R2</b>	IP20	2	570 x 180 x 330 - (11)	117%	19.2	3600

Inverters ratings 0.75 ~ 30kW have a built-in braking transistor. For applications requiring a greater braking torque an external braking resistor can be connected to terminals B1 / P and B2 (or P2 / B1 and B2); for inverter ratings above 30 kW an external braking unit BU-2\_4 series (connected to (P1) / (-) of the inverter) and a braking resistor (connected to BR+ / BR- terminals of braking unit) is required.

(1): Minimum resistance is the acceptable minimum value of the braking resistor for a single braking unit.

# VDI100 GENERAL PURPOSE FULL VECTOR INVERTER

## EMI FILTERS

Code	Model	Dimensions: WxHxD (mm)	Weight (kg)	For VDI100-....	Code	Model	Dimensions: WxHxD (mm)	Weight (kg)	For VDI100-....
<b>Overload HD (150%) - Class 400V 3ph</b>									
S7GHL	EMI-FTF-480-7	190 x 40 x 70	0.6	1007	S7GHL	EMI-FTF-480-7	190 x 40 x 70	0.6	1007
S7GHL	EMI-FTF-480-7	190 x 40 x 70	0.6	1015	S7GHL	EMI-FTF-480-7	190 x 40 x 70	0.6	1015
S7GHL	EMI-FTF-480-7	190 x 40 x 70	0.6	1022	S7GHO	EMI-FTF-480-16	250 x 45 x 70	0.8	1022
S7GHO	EMI-FTF-480-16	250 x 45 x 70	0.8	2037	S7GHO	EMI-FTF-480-16	250 x 45 x 70	0.8	2037
S7GHO	EMI-FTF-480-16	250 x 45 x 70	0.8	2055	S7GHP	EMI-FTF-480-30	270 x 50 x 85	1	2055
S7GHO	EMI-FTF-480-16	250 x 45 x 70	0.8	3075	S7GHP	EMI-FTF-480-30	270 x 50 x 85	1	3075
S7GHP	EMI-FTF-480-30	270 x 50 x 85	1	3110	S7GOA	EMI-FTF-480-42	310 x 50 x 85	1.3	3110
S7GHP	EMI-FTF-480-30	270 x 50 x 85	1	3150	S7GOB	EMI-FTF-480-55	250 x 85 x 90	1.9	3150
S7GHP	EMI-FTF-480-30	270 x 50 x 85	1	4150	S7GOB	EMI-FTF-480-55	250 x 85 x 90	1.9	4150
S7GOA	EMI-FTF-480-42	310 x 50 x 85	1.3	4185	S7GOC	EMI-FTF-480-75	270 x 80 x 135	2.6	4185
S7GOB	EMI-FTF-480-55	250 x 85 x 90	1.9	4220	S7GOC	EMI-FTF-480-75	270 x 80 x 135	2.6	4220
S7GOC	EMI-FTF-480-75	270 x 80 x 135	2.6	5300	S7GOD	EMI-FTF-480-100	270 x 90 x 150	3	5300
S7GOC	EMI-FTF-480-75	270 x 80 x 135	2.6	5370	S7GOE	EMI-FTF-480-130	270 x 90 x 150	3.6	5370
S7GOD	EMI-FTF-480-100	270 x 90 x 150	3	5450	S7GOF	EMI-FTF-480-180	400 x 120 x 170	6.2	5450

Install an EMC filter on power supply side to eliminate noise transmitted between the power line and the inverter.

The inverter EMI filter above meets the EN 61800-2004/A1:2012 specification.

Inverter can be ordered with EMC filter (-F models).

VDI100-...-2T (230V Class) models are not provided with internal / external filters.

### A. VDI100-...-4-F series with EMC filter (-F models)

VDI100-...-4-F series inverters are equipped with an EMC filter able to guarantee the performance levels required by EN 61800:2004/A1:2012 standard:

- sizes 1007 to 3110: category C2 with a maximum of 10 meters of shielded motor cable;
- sizes 4150 to 5450: category C3 with a maximum of 10 meters of shielded motor cable.

### B. External Input EMI Filter

VDI100-...-4 series inverters equipped with external filter above, are able to guarantee the performance levels required by EN 61800:2004/A1:2012 standard, with the same behaviour of above filter.

# ACCESSORIES AND OPTIONS

## OTHER OPTIONS

Code	Model	Description
<b>Communication</b>		
<b>S6N297</b>	<b>EXP-PDP-VDI100</b>	Profinet interface internal expansion card
<b>S6N298</b>	<b>EXP-CAN-VDI100</b>	CanBus interface internal expansion card
<b>S6N299</b>	<b>EXP-CAT-VDI100</b>	EtherCAT interface internal expansion card
<b>S6N220</b>	<b>EXP-DN-BDI/VDI</b>	DeviceNet interface external module
<b>Encoder cards</b>		
<b>S6N222</b>	<b>EXP-LD-VDI100</b>	Digital incremental Line driver encoder card
<b>S6N223</b>	<b>EXP-OC-VDI100</b>	Digital incremental open collector encoder card
<b>S6N224</b>	<b>EXP-LD-PM-VDI100</b>	Digital incremental line driver encoder card for Permanent Magnet motor (*)
<b>S6N225</b>	<b>EXP-RS-PM-VDI100</b>	Resolver card for Permanent Magnet motor and Asynchronous (*)
<b>S6N226</b>	<b>EXP-SC-PM-VDI100</b>	SinCos encoder card for Permanent Magnet motor (*)
(*): installation on VDI100 sizes 2 and higher		
<b>Others</b>		
<b>S6N228</b>	<b>Memory KB-BDI/VDI</b>	Copy unit
<b>S6N229</b>	<b>Cable RJ45 to USB 1.8m</b>	RJ45 to USB connecting cable (1.8 m. length)
<b>S6N231</b>	<b>KB-LCD-VDI100</b>	LCD keypad
<b>S6N233</b>	<b>KB-BLI-VDI100</b>	Blind cover
<b>S6N234</b>	<b>KB cable 1m</b>	Keypad extension cable 1 m
<b>S6N235</b>	<b>KB cable 2m</b>	Keypad extension cable 2 m
<b>S6N236</b>	<b>KB cable 3m</b>	Keypad extension cable 3 m
<b>S6N237</b>	<b>KB cable 5m</b>	Keypad extension cable 5 m
<b>S6N242</b>	<b>Protective cover VDI100 Size 1</b>	Protective cover for VDI100 Size 1
<b>S6N243</b>	<b>Protective cover VDI100 Size 2</b>	Protective cover for VDI100 Size 2
<b>S6N244</b>	<b>Protective cover VDI100 Size 4</b>	Protective cover for VDI100 Size 4
<b>S6N302</b>	<b>MLC-S1-VDI100</b>	Middle layer case for expansion card (size 1)
<b>S6N303</b>	<b>MLC-S2-VDI100</b>	Middle layer case for expansion card (size 2)
<b>S6N304</b>	<b>MLC-S3-VDI100</b>	Middle layer case for expansion card (size 3)
<b>S6N305</b>	<b>MLC-S4-VDI100</b>	Middle layer case for expansion card (size 4)
<b>S6N300</b>	<b>EXP-I/O-VDI100</b>	Digital & analog I/O Expansion card
<b>S6N301</b>	<b>EXP-24V-VDI100</b>	DC24V power supply card

# SOFTWARE

## GF-eXpress PROGRAMMING SOFTWARE

### Applications

- > Configuring parameters of Gefran devices (Instruments, Drives, Sensors)
- > Tuning control parameters with on-line tests and trends
- > Managing parameter archive for multiple configuration.

### Features

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>&gt; Guided product selection</li> <li>&gt; Multiple languages</li> <li>&gt; Creation and storage of recipes</li> <li>&gt; Oscilloscope</li> </ul> | <ul style="list-style-type: none"> <li>&gt; Simplified settings</li> <li>&gt; Parameter printout</li> <li>&gt; Network autoscan</li> </ul> |
|---|--|

GF\_eXpress software configures the parameters of the automation components, drives and sensors in the Gefran catalogue.


The graphic interface makes selecting and configuring parameters easy and intuitive. Devices are grouped according to product type and functions.

Products are searched by means of a context search and a display of product photos.

This provides a single device library for all Gefran products.

Complete configuration information for every device is given in XML format to facilitate expansion of the catalogue and parameters.





#### GEFRAN DEUTSCHLAND GmbH

Philipp-Reis-Straße 9a  
D-63500  
Seligenstadt  
Ph. +49 (0) 61828090  
Fax +49 (0) 6182809222  
vertrieb@gefran.de

#### SIEI AREG - GERMANY

Gottlieb-Daimler Strasse 17/3  
D-74385  
Pleidelsheim  
Ph. +49 (0) 7144 897360  
Fax +49 (0) 7144 8973697  
info@sieiareg.de

#### SENSORMATE AG

Steigweg 8,  
CH-8355 Aadorf, Switzerland  
Ph. +41(0)52-2421818  
Fax +41(0)52-3661884  
<http://www.sensormate.ch>

#### GEFRAN FRANCE SA

PARC TECHNOLAND  
Bâtiment K - Zi Champ Dolin  
3 Allée des Abruzzes  
69800 Saint-Priest  
Ph. +33 (0) 478770300  
Fax +33 (0) 478770320  
commercial@gefran.fr

#### GEFRAN BENELUX NV

ENA 23 Zone 3, nr. 3910  
Lammerdries-Zuid 14A  
B-2250 OLEN  
Ph. +32 (0) 14248181  
Fax +32 (0) 14248180  
info@gefran.be

#### GEFRAN UK Ltd

Clarendon Court  
Winwick Quay  
Warrington  
WA2 8QP  
Ph. +44 (0) 8452 604555  
Fax +44 (0) 8452 604556  
sales@gefran.co.uk

#### GEFRAN MIDDLE EAST

Yeşilköy Mah. Atatürk Cad.  
EGS Business Park  
No:12 B1 Blok K:12 D:393  
Bakırköy/Istanbul/TÜRKİYE  
Ph. +90 212 465 91 21  
Fax +90 212 465 91 22  
info@gefran.com.tr

#### GEFRAN SIEI

Drives Technology Co., Ltd  
No. 1285, Beihe Road, Jiading  
District, Shanghai,  
China 201807  
Ph. +86 21 69169898  
Fax +86 21 69169333  
info@gefran.com.cn

#### GEFRAN SIEI - ASIA

31 Ubi Road 1  
#02-07  
Aztech Building,  
Singapore 408694  
Ph. +65 6 8418300  
Fax +65 6 7428300  
info@gefran.com.sg

#### GEFRAN INDIA

Survey No. 191/A/1,  
Chinchwad Station Road,  
Chinchwad,  
Pune-411033, Maharashtra  
Ph. +91 20 6614 6500  
Fax +91 20 6614 6501  
gefran.india@gefran.in

#### GEFRAN Inc.

400 Willow Street  
North Andover, MA  
01845 USA  
Toll Free 1-888-888-4474  
Fax +1 (617) 340 2761  
info.us@gefran.com

#### GEFRAN BRASIL ELETROELETRÔNICA

Avenida Dr. Altino Arantes,  
377 Vila Clementino  
04042-032 SÃO PAULO - SP  
Ph. +55 (0) 1155851133  
Fax +55 (0) 1132974012  
comercial@gefran.com.br

#### GEFRAN HEADQUARTER

Via Sebina, 74  
25050 PROVAGLIO D'ISEO (BS) ITALY  
Ph. +39 03098881  
Fax +39 0309839063

#### GEFRAN DRIVES AND MOTION S.R.L.

Via Carducci, 24  
21040 GERENZANO (VA) ITALY  
Ph. +39 02967601  
Fax +39 029682653  
info.motion@gefran.com  
Technical Assistance:  
technohelp@gefran.com  
Customer Service  
salesmotion@gefran.com



[www.gefran.com](http://www.gefran.com)

**GEFRAN**  
BEYOND TECHNOLOGY